

**60-X5
SPRAYWAX SOLUTION**

PRODUCT DESCRIPTION

Spraywax solution is a light duty, liquid wax release agent. It is formulated with natural waxes to reduce the tendency of fisheyes. It is fast drying, easy to apply and buffs to a high polish. It may be used to facilitate release or add a gleam to finished FRP parts and many other surfaces.

- **QUICK, EASY RELEASE OF PARTS**
- **EASY APPLICATION AND BUFFING**
- **COST AND LABOR SAVINGS**
- **CONVENIENT HANDLING PROCEDURES SAVE TIME AND LABOR**

SHAKE WELL BEFORE USING

TYPICAL PHYSICAL CHARACTERISTICS (all tests at 77° F.)

The shelf life and product specifications are listed for reference guide only. Certain batches will not conform exactly to the shelf life and product specifications because storage conditions, temperature change, age and testing equipment can each have a significant effect on the test results. *Products outside of this shelf life can perform acceptably.*

60-X5

Weight Per Gallon:	6.6 lbs/gal
Flash Point:	37° Fahrenheit
VOC (EPA Method 24):	711 grams/liter
Shelf Life:	One year from date of shipment

APPLICATION SUGGESTIONS

Spray wax solution is best applied by spraying evenly over the mold surface, work in with a clean rag, allow to dry and buff. It may also be applied by cloth. Apply a wet coat of Spraywax solution with a cloth. After a few moments of drying, a light haziness appears. Light buffing with soft toweling then produces a high gloss on the tooling or finished parts.